



Staticide® 4000 Acrylic Floor Finish

High solids, value added

ACL Staticide® 4000 Acrylic Dissipative Floor Finish is a value-added solution that provides advanced static protection at an affordable price. This budget-friendly formula delivers a resilient, glossy finish that lasts up to twelve months. It is a popular choice for economically conscious companies that do not want to sacrifice performance.

This product is advantageous for contract manufacturers or businesses that do not own their premises, offering a low-cost investment for maintaining static-free environments. The water-based formula is not only cost-effective, but also meets stringent safety and environmental standards.

This water-based formula is UL-listed for slip resistance, RoHS and REACH-compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, and acids.

Directions:

Clean floor and apply two to three thin coats of floor finish with a dedicated lint-free mop. Wait a minimum of one hour between coats. See application instructions for details.

Maintenance:

Sweep or dust mop daily. Do not use sweeping compound. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use Staticide® 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product# 40001: 4 gallons per case

Product# 40005: 5 gallon pail

Product# 40002: 54 gallon drum

Ideal for the following applications:

- Electronic repair facilities
- Contract manufacturing
- Laboratories
- Shipping and production areas
- Static-sensitive warehousing and data centers

FEATURES

- ✿ Suitable for floor specifications outlined in ANSI/ESD S20.20
- ✿ Surface Resistance: $10^9 - 10^9$ ohms @ 100v and 12% RH
- ✿ VOC : < 4%
- ✿ Solids: 20% ± 5%
- ✿ Coverage: 1500 - 2000 square feet per gallon
- ✿ UL listed for slip resistance
- ✿ Use on VCT, linoleum, or ceramic tile
- ✿ Strip cycle is 6 - 12 months
- ✿ Made in USA

