



Staticide® 4600 Ultra Dissipative Floor Finish

High quality, high performance

No other ESD floor finish can match ACL Staticide® 4600 Ultra Dissipative Floor Finish for electrical properties, physical longevity, and gloss. The formula features superior abrasion resistance and durability, fortifying floors with a shiny, ESD-safe, long-lasting protective layer for 12 to 24 months.

By maximizing stripping cycles, companies can decrease costs by eliminating annual labor fees and production shutdowns. Its reliability makes Staticide® 4600 Ultra an ideal choice for companies implementing a static protection facility complying to ANSI/ESD S20.20.

The water-based formula is UL-listed for slip resistance, RoHS and REACH-compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, and acids.

Directions:

Clean floor and apply two to three thin coats of floor finish with a dedicated lint-free mop. Wait a minimum of one hour between coats. See application instructions for details.

Maintenance:

Sweep or dust mop daily. Do not use sweeping compound. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use Staticide® 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product# 4600-1: 4 gallons per case

Product# 4600-5: 5-gallon pail

Product# 4600-2: 54 gallon drum

Ideal for the following applications:

- Electronics manufacturing and assembly
- Sensitive device manufacturing
- Medical and cleanroom facilities
- ESD workspaces
- Static-sensitive warehousing and data centers

FEATURES

- ✿ Suitable for floor specifications outlined in ANSI/ESD S20.20
- ✿ Surface Resistance: 10^7 - 10^9 ohms @ 100v and 12rH
- ✿ VOC : < 4%
- ✿ Solids: $22\% \pm 5\%$
- ✿ Coverage: 1500 - 2000 square feet per gallon
- ✿ UL listed for slip resistance
- ✿ Use on VCT, linoleum, or ceramic tile
- ✿ Strip cycle is 12 - 24 months
- ✿ Made in USA



ACL Staticide®

840 W. 49th Place · Chicago, IL 60609
800.782.8420 · 847.981.9212 · fax 847.981.9278
info@aclstaticide.com · www.aclstaticide.com



ACL, Inc. has been certified by
DQS Inc. to ISO-9001 : 2015
Certificate NO. 10002746