

SAFETY DATA SHEET


STATICIDE® Anti-Static Floor Stripper

SECTION 1: Identification

```
1.1. Product identifier
  Trade name
     STATICIDE® Anti-Static Floor Stripper
  Product no.
     4010-1, 4010-2, 4010-5, 4010-Q
1.2. Relevant identified uses of the substance or mixture and uses advised against
  Relevant identified uses of the substance or mixture
     Cleaning product, Used to remove water-based floor finishes
     Restricted to professional users.
  Uses advised against
     None known.
1.3. Details of the supplier of the safety data sheet
  Company and address
     ACL Staticide
     840 W. 49th Place
     IL 60609 Chicago
     USA
     T: +1 847.981.9212
     Fax: +1 847.981.9278
     www.aclstaticide.com
  E-mail
     marykay@aclstaticide.com
  SDS date
     8/16/2024
  SDS Version
     1.0
1.4. Emergency telephone number
  INFOTRAC (01) 800.535.5053 (day or night)
SECTION 2: Hazard(s) identification
OSHA/HCS status
  This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)
2.1. Classification of the substance or mixture
  Skin Corr. 1B; H314, Causes severe skin burns and eye damage.
  Eye Dam. 1; H318, Causes serious eye damage.
```

2.2. Label elements

Hazard pictogram(s)



Precautionary statement(s)

General



Prevention

Do not breathe vapour/mist. (P260)

Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. (P301+P330+P331) IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. (P303+P361+P353) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338) Immediately call a POISON CENTER/doctor. (P310)

Storage

Disposal

Dispose of contents/container in accordance with local regulation (P501) Additional labelling

Not applicable.

2.3. Other hazards

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
2-butoxyethanol; ethylene	CAS No.: 111-76-2	3-5%	Acute Tox. 4, H302	
glycol monobutyl ether			Skin Irrit. 2, H315	
			Eye Irrit. 2, H319	
			Acute Tox. 3, H331	
disodium metasilicate	CAS No.: 6834-92-0	3-5%	Met. Corr. 1, H290	
			Skin Corr. 1B, H314	
			Eye Dam. 1, H318	
Alcohols, C9-11, ethoxylated	CAS No.: 68439-46-3	3-5%	Acute Tox. 4, H302	
			Eye Dam. 1, H318	
2-aminoethanol;ethanolamine	e CAS No.: 141-43-5	1-3%	Acute Tox. 4, H302	
			Acute Tox. 4, H312	
			Skin Corr. 1B, H314	
			Acute Tox. 4, H332	
tetrasodium ethylene diamine	e CAS No.: 64-02-8	0-2%	Acute Tox. 4, H302	
tetraacetate			Eye Dam. 1, H318	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

SECTION 4: First-aid measures

4.1. Description of first aid measures

General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Flush exposed area with water for a long time - at least 30 minutes. It may be necessary to flush for several hours. Use a comfortable water temperature (20-30 °C). Contact Poison Information/doctor/hospital for further advice on follow-up and treatment.

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with plenty of water or salt water (20-30 °C) for at least 30 minutes and continue until irritation stops. Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x) Carbon oxides (CO / CO2)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous



earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid direct contact with the product. Avoid contact during pregnancy and while nursing. Smoking, drinking and consumption of food is not allowed in the work area. See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep container tightly closed and sealed until ready for use.

Storage conditions

Protect from sunlight. Dry, cool and well ventilated Room temperature 15 to 25°C

Incompatible materials

Strong acids and oxidizers

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol; ethylene glycol monobutyl ether Long term exposure limit (OSHA Table Z-1) (mg/m³): 240 Long term exposure limit (OSHA Table Z-1) (ppm): 50 Long term exposure limit (ACGIH TLV) (ppm): 20

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Ensure that eyewash stations and safety showers are located within easy reach.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only protective equipment with a recognized certification mark, e.g. the UL mark. Respiratory Equipment ACL**Staticide**.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

Туре	Class	Colour	Standards	
Deenigstrangen to the		coloui		
Respiratory protection is not needed in the event of adequate ventilation.				
Skin protection				
Work situation	Recommended	Type/Category	Standards	
When there is risk of	Dedicated work clothing	-	-	0
splash- / intermittent exposure	should be worn.			R
Hand protection				
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	-	EN374-2	
Eye protection				
Work situation	Туре	Standards	5	
When there is risk of splash- / intermittent exposure	Safety glasses with side sh	nields. EN166		
ECTION 9: Physical and ch		perties		
I. Information on basic pl Physical state Liquid Color Red Odor Solvent Odor threshold (ppm) No relevant or availab pH <12 pH in solution (4:1%) Density (g/cm ³)		re of the product.		

ACL**Staticide**

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

No relevant or available data due to the nature of the product. Relative vapor density No relevant or available data due to the nature of the product. Decomposition temperature (°F) No relevant or available data due to the nature of the product. Data on fire and explosion hazards Flash point (°F) No relevant or available data due to the nature of the product. Flammability (°F) The material is not combustible. Auto-ignition temperature (°F) No relevant or available data due to the nature of the product. Explosion limits (% v/v) No relevant or available data due to the nature of the product. Solubility Solubility in water Completely soluble n-octanol/water coefficient (LogKow) No relevant or available data due to the nature of the product. Solubility in fat (q/L) No relevant or available data due to the nature of the product. 9.2. Other information VOC (g/L) 100 Other physical and chemical parameters No data available. Oxidizing properties No relevant or available data due to the nature of the product. SECTION 10: Stability and reactivity 10.1. Reactivity No data available. 10.2. Chemical stability The product is stable under the conditions, noted in section 7 "Handling and storage". 10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies None known. 10.4. Conditions to avoid Keep out of reach of children 10.5. Incompatible materials

Strong acids and oxidizers

10.6. Hazardous decomposition products Thermal decomposition may produce corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

ACL**Staticide**.

Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

Tissue-damaging effects: This product contains substances with skin corrosive properties. Inhaled vapour or aerosols may produce adverse effects to lungs, irritations and burns in the respiratory organs as well as coughing. Dermal contact and contact with the eye cause irreversible effects.

Other information

2-butoxyethanol; ethylene glycol monobutyl ether has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

- 12.3. Bioaccumulative potential
 - Based on available data, the classification criteria are not met.
- 12.4. Mobility in soil
- No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

- 12.6. Other adverse effects
 - None known.

SECTION 13: Disposal considerations

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	UN1760	OCORROSIVE LIQUID, N.O.S. (2- aminoethanol;ethanolamine, disodium metasilicate)	Transport hazard class: 8 Label: 8 Classification code: C9	III	No	Limited quantities: 5 L Tunnel restriction code: (E) See below for additional information.
IMDG	UN1760	OCORROSIVE LIQUID, N.O.S. (2- aminoethanol;ethanolamine, disodium metasilicate)	Transport hazard class: 8 Label: 8 Classification code: C9	III	No	Limited quantities: 5 l EmS: F-A S-B See below for additional



	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
			B			information.
ΙΑΤΑ	UN1760	CORROSIVE LIQUID, N.O.S. (2- aminoethanol;ethanolamine, disodium metasilicate)	Transport hazard class: 8 Label: 8 Classification code: C9	III	No	See below fo additional information.
* Packing	group					
incide IMDC trans IATA trans This J 14.6. Sp Not a 14.7. Tra	ents or ac G / See se port. / See Tab port. product is recial pre- applicable	n bulk according to IMO instruments	pecial provisions, requirements, o provisions, requirements, or wa ransport of dangerous goods.	or warnings	in conn	ection with
SECTIO	0N 15: Reg	gulatory information				
15.2. U. TSCA 2- Clear N EPCR N EPCR N CERC	S. Federa (the non butoxyet A r Air Act one of th A Section one of th A section one of th A section one of th	e components are listed 1 304 e components are listed		ce or mixtu	re	
State re Califo Mass 2- New 2-	gulations ornia / Pro one of th achusett butoxyet Jersey / R butoxyet	5	ner / Substance number: 0275	rd Substand	e List	
	York / Ric	ght To Know Act				

2-butoxyethanol; ethylene glycol monobutyl ether is listed

NFPA Health hazard: 2 Fire hazard: 0 Instability hazard: 0 Specific hazard: 0

15.4. Restrictions for application

Restricted to professional users. Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H290, May be corrosive to metals.

- H302, Harmful if swallowed.
- H312, Harmful in contact with skin.
- H314, Causes severe skin burns and eye damage.
- H315, Causes skin irritation.
- H318, Causes serious eye damage.
- H319, Causes serious eye irritation.
- H331, Toxic if inhaled.
- H332, Harmful if inhaled.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act



SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

The safety data sheet is validated by

Mary Kay Botkins

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en