



## 4500 Staticide® ESD Polycoat Sealer

### *Durable static control polyurethane*

ACL Staticide® ESD Polycoat Sealer offers superior static control with remarkable durability. This water-based polyurethane coating delivers consistent resistance readings between 10e6 to 10e9 ohms regardless of humidity.

Once applied to the floor, this single-part system will complete a circuit by providing a swift and safe path-to-ground. Designed for interior concrete floors, this ESD coating is perfectly suited for temporary ESD work spaces, data centers, warehouses, and creating Faraday cages. Its reliability makes Staticide ESD Polycoat Sealer an ideal choice for companies implementing a static protection facility complying to ANSI/ESD S20.20.

The Staticide ESD Polycoat Sealer is resistant to yellowing, dirt attraction, and UV fading. The durable finish withstands alcohol, oils, gasoline, and most common electronic chemicals.

#### Directions:

*Stir and mix before using. Must apply to a clean dry surface. See application instructions for details.*

#### Maintenance:

Sweep or dust mop daily. Do not use sweeping compound. Damp mop weekly using water or 4040 Universal Cleaner Degreaser. Remove spills immediately.

#### Ideal for the following applications:

- Electronics manufacturing and assembly
- Sensitive device manufacturing
- Contract manufacturing
- ESD workspaces
- Static-sensitive warehousing and data centers

#### FEATURES

- ✿ Suitable for floor specifications outlined in ANSI/ESD S20.20
- ✿ Resistance: 10<sup>5</sup> - 10<sup>8</sup> ohms when tested to ANSI/ESD STM7.1
- ✿ Water-based polyurethane with zero VOC
- ✿ Reduces tribogeneration
- ✿ Coverage: 200 - 250 square feet per gallon
- ✿ Translucent with a bluish hue
- ✿ For concrete or unfinished wood
- ✿ High durability
- ✿ Made in USA

**Product# 4500-1:** 1-gallon pail

**Product# 4500-5:** 5-gallon pail