SDS #63006400 Page 1 of 9 Rev. January 7, 2016

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 1 CHEMICAL PRODUCT SECTION

STATICIDE® ESD Safety Shield Identification: Product Name:

> #63001, 63005, 6300S, 64001, 64005, 6400S Product Number:

Product description: Electrostatic dissipative coating for interior use on hard surfaces

Product type: Acrylic liquid mixture

Industrial applications, professional applications. Interior use Application:

ACL Incorporated Manufacturer:

840 W. 49th Place Chicago, IL 60609

PH: (01) 847.981.9212 [U.S.A.] FAX: (01) 847.981.9278 [U.S.A.]

Emergency telephone: US/Canada Emergency Telephone:

INFOTRAC: (01) 800.535.5053 (day or night)

International Emergency Telephone: INFOTRAC: 352.323.3500 (day or night)

Section 2 HAZARD IDENTIFICATION

Emergency Overview: Caution: Contents under pressure. US OSHA Hazard Classification: Irritant, Target organ effects

Potential Health Effects: Prolonged overexposure may damage the nervous system, blood and blood forming

organs, kidneys and liver.

2.1 Classification of the substance or mixture

Product definition: Mixture

Physical: None

Health: Eye irritation / category 2B

Skin irritation / category 2

Environmental: None

2.2 Label Elements

Hazard Pictograms:



Signal Word: Warning

Hazard Statement:

Causes skin and eye irritation (H315 + H320)

Precautionary Statements:

General:

If medical advice is needed, have container or label at hand (P101)

Keep out of reach of children (P102)

Read label before use (P103)

Prevention:

Wash hands thoroughly after handling (P264)

Response:

IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing (P305 +P351 + P338)

If eye irritation persists, get medical attention or advice (P337 + P313)

IF ON SKIN, wash with plenty of water. (P302 + P352)

If skin irritation occurs, get medical attention or advice (P332 + P313)

Unknown Acute Toxicity: No data available

Section 3	INFORMATION ON INGREDIENTS		
CHEMICAL	C.A.S.	Weight %	GHS Classification
2-Butoxyethanol	111-76-2	6 - 10	Flam. Liq. 4; H227
•			Acute Tox. 4; H302 + H312 + H332
			Skin Irrit. 2; H315
			Eye Irrit. 2A; H319
Diethylene Glycol Butyl Ether	112-34-5	1 - 5	Eye Irrit. 2A; H319
Diethylene Glycol	111-46-6	1 - 5	Acute Tox. 4; H302
, ,			STOT RE 2; H373
Acrylic Resin Blend	Proprietary	3 - 8	Not hazardous
Wetting agent	Proprietary	trace amount	Not hazardous
Water	7732-18-5	75 - 85	Not hazardous
[a			

Section 4 FIRST AID MEASURES

4.1 Description of first aid measures

General Advice: If exposed or concerned: Get medical advice/attention

Inhalation: Remove affected person from source of exposure. If breathing is difficult or symptoms of irritation persist, get medical attention.

Eye Contact: Immediately flush eyes with water for at least 15 minutes. Hold eyelids open during the water flushing. GET MEDICAL ATTENTION.

Skin Contact: Quickly remove contaminated clothing and wash immediately with plenty of soap and water. Get medical attention if irritation or symptoms develop. Launder contaminated clothing before reuse.

Ingestion: If the patient is conscious, rinse mouth with water. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Wear gloves

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Section 5 FIRE FIGHTING MEASURES	Section 5 FIRE FIGHTING MEASURES	
----------------------------------	----------------------------------	--

Protective equipment and precautions for firefighters:

5.1 Extinguishing media

Suitable extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: Not determined

- **5.2 Special hazards arising from the substance or mixture:** Thermal decomposition products may be hazardous. **Hazardous Combustion Products:** Oxides of carbon, nitrogen, sulfur and unknown materials.
- **5.3 Advice for firefighters:** This product is not flammable or combustible. Use any media that is appropriate for the surrounding fire. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.
- **5.4 Further information:** No data available

Section 6

ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. For personal protection see section 8.

6.2 Environmental precautions

No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Containment: Prevent further leakage or spillage if safe to do so. Halt spill at source and contain or dike spill with inert absorbent material.

Clean up: Transfer liquid to containers for recovery or disposal. Shovel absorbent into drums for disposal in accordance with local, state and federal regulations.

6.4 Reference to other sections

For disposal see section 13.

Section 7

HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice.. Keep containers closed when not in use. For precautions see section 2.2

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place away from direct sunlight. Store in cool, dry, area away form excessive heat and incompatible

Storage Conditions: Ambient $(40^{\circ} - 90^{\circ} \text{ F})$

Incompatible Materials: None known based on information supplied.

7.3 Specific end use(s) Apart from the uses mentioned in section 1.2

Designed for static control areas in electronics manufacturing.

Section 8

EXPOSURE CONTROL / PERSONAL PROTECTION

8.1 Control parameters

Occupational exposure limits

EXPOSURE LIMITS				
Chemical Name OSHA PEL ACGIH TLV DFG UK WEL				
2-Butoxyethanol	50 ppm (skin) TWA	20 ppm (skin) TWA	10 ppm TWA (skin) MAK	25 ppm TWA 50 ppm STEL
Diethylene Glycol Butyl Ether	NE	NE	$100 \text{ Mg/m}^3 \text{MAK}$	NE
Diethylene Glycol	NE	NE	10 ppm MAK	NE

^{*}listed undr Aliphatic Hydrocarbon Gasses; Alkane C1-C4

Page 4 of 9

SDS #63006400 Rev. January 7, 2016

8.2 Exposure controls

Appropriate engineering controls

Engineering Controls: Use with adequate general or local exhaust ventilation to minimize exposure levels. General ventilation is expected to be adequate unless product is heated or aerosols are formed in use.

Individual protection measures, such as personal protective equipment

Hygiene measures: Wash hands before eating, smoking and using the lavatory and at the end of the working period. When using, do not eat or drink. When using, do not smoke.

Eye Protection: Chemical safety goggles recommended.

Skin Protection: Avoid prolonged or repeated skin contact. Impervious gloves such as nitrile, neoprene or rubber are

recommended.

Hand protection: Gloves Recommended.

Respiratory protection: None required in well ventilated areas. An approved organic vapor full face respirator is

advised for poorly ventilated areas.

Environmental exposure controls: For normal conditions, protection is not necessary.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Translucent blue liquid
Odor	Reminiscent of ether
Odor threshold	Not determined
pH	2.5
Melting point/freezing point	Not determined
Initial boiling point and boiling range	>212F / 100°C
Flash point and method	> 200°F (93.3° C) estimated
Evaporation rate (butyl acetate = 1)	.1 (2-butoxyethanol)
Flammability (solid, gas, liquid)	Not flammable
Upper/lower flammability or explosive limits	Lower: 1.1% (2-butoxyethanol) Upper: 10.8% (Diethylene glycol)
Vapor pressure	0.6 mmHg@ 20C (2-butoxyethanol)
Vapor density (air=1)	>7.75
Relative density	Not determined
Solubility(ies).	Soluble
Partition coefficient: n-octanol/water	Not determined
Autoignition temperature	>392F / 200°C
Decomposition temperature	Not determined
Viscosity (kinematic)	Not determined
Volatile by weight	: >60%

9.2 Other safety information

VOC	1.15lb/gal

Section 10 STABILITY AND REACTIVITY

- **10.1 Reactivity** Stable under recommended storage conditions.
- **10.2** Chemical stability Stable under recommended storage conditions.
- 10.3 Possibility of hazardous reactions None under normal procession
- 10.4 Conditions to avoid: Heat, flames and sparks. Extremes of temperature and direct sunlight.
- **10.5 Incompatible materials:** Strong acids, strong bases, oxidizing agents, amines.
- 10.6 Hazardous decomposition products: Hazardous Polymerization will not occur.

Combustion may produce carbon monoxide, carbon dioxide, Oxides of nitrogen, unknown materials.

Other decomposition products: In the event of fire: see section 5

Section 11 TOXICOLOGY INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose
Butyl Cellusolve	LC ₅₀ dermal	Rabbit	1,060 mg/kg
111-76-2	LD ₅₀ oral	Rat	880 mg/kg
Diethylene Glycol Butyl Ether	LC ₅₀ dermal	Rabbit	2,764 mg/kg
112-34-5	LD ₅₀ oral	Rat	7,291 mg/kg
Diethylene Glycol	LC ₅₀ dermal	Rabbit	11,890 mg/kg
111-46-6	LD ₅₀ oral	Rat	12,565 mg/kg

Conclusion/Summary: Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Exposure
Butyl Cellusolve	Eye irritation	Rabbit	24 hours
111-76-2	skin irritation	Rabbit	20 hours
Diethylene Glycol Butyl Ether	Eye irritation	Rabbit	(OECD Test Guideline 405)
112-34-5	Mild skin irritation	Rabbit	1 hours
Diethylene Glycol	No eye irritation	Rabbit	
111-46-6	No skin irritation	Rabbit	(OECD Test Guideline 404)

Conclusion/Summary: Not available

Sensitization

Product/ingredient name	Result	Species	Test
Butyl Cellusolve	Does not cause skin	Guinea Pig	OECD Test
111-76-2	sensitization		Guideline 406
Diethylene Glycol Butyl	Does not cause skin	Guinea Pig	OECD Test
Ether 112-34-5	sensitization		Guideline 406
Diethylene Glycol	Does not cause sensitization on	Guinea Pig	Maximisation Test
111-46-6	laboratory animals		(GPMT)

Conclusion/Summary: Not available.

Mutagenicity

Product/ingredient name	Result	Species	Test
Butyl Cellusolve	Result: negative	Mouse, male	Method: OECD Test
111-76-2			Guideline 474
Diethylene Glycol Butyl Ether	Negative	Drosophila melanogaster	OECD Test
112-34-5		- male and female	Guideline 477
	Negative	S. typhimurium	Ames Test
Diethylene Glycol	No data available		
111-46-6			

Conclusion/Summary: Not available.

Carcinogenicity Conclusion/Summary:

IARC: Butyl Cellusolve / 3 - Group 3: Not classifiable as to its carcinogenicity to humans

Diethylene Glycol Butyl Ether is not present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Butyl Cellusolve: Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Page 6 of 9

Diethylene Glycol Butyl: No adverse effect has been observed in chronic toxicity tests.

Diethylene Glycol: No data available **Conclusion/Summary:** Not available.

<u>Teratogenicity</u> <u>Conclusion/Summary:</u> Not available. <u>Specific target organ toxicity (single exposure):</u>

Specific target organ toxicity (repeated exposure): Not available.

Aspiration hazard: Not available.

Information on the likely routes of exposure: Not available.

Section 12

ECOLOGICAL INFORMATION

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Butyl Cellusolve	LC50 > 1474 mg/l	Oncorhynchus mykiss (rainbow trout)	96 hours
111-76-2	Immobilization EC50 > 1515 mg/l	Daphnia (water flea) Pseudokirchneriella subcapitata (green algae)	48 hours
	Growth inhibition EC50 >		72 hours
Diethylene Glycol Butyl	LC50 > 1300 mg/l	Lepomis macrochirus	96 hours
Ether 112-34-5	EC50 > 100 mg/l	Daphnia magna (water flea)	48 hours
	EC50 > 100 mg/l	Desmodesmus subpicatus	96 hours
	LC50 1170 mg/l	Pseudomonas putida	16 hours
Diethylene Glycol	LC50 > 75,200 mg/l	Pimephales promelas (fathead minnow)	96 hours
111-46-6	LC50 > 5,000 mg/l	Carassius auratus (goldfish)	24 hours
	LC50 > 10,000 mg/l	Daphnia magna (water flea)	24 hours

Conclusion/Summary: Not available

12.2 Persistence and degradability

	1112 I DISSOUND WING WORK WARNING			
Product/ingredient name	Test	Result	Dose	Inoculum
Butyl Cellusolve	OECD Test Guideline 301B	90.4 %	-	-
111-76-2				
Diethylene Glycol Butyl	OECD Test Guideline 301B	91.7%	-	-
Ether 112-34-5				
Diethylene Glycol	OECD Test Guideline 301B	90 – 100%	-	-
111-46-6				

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Butyl Cellusolve	-	-	Readily biodegradable
111-76-2			
Diethylene Glycol Butyl	-	-	Readily biodegradable
Ether 112-34-5			
Diethylene Glycol	-	-	Readily biodegradable
111-46-6			

Conclusion/Summary: Not available

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Butyl Cellusolve 111-76-2	No data	-	Not likely
Diethylene Glycol Butyl Ether 112-34-5	No data	-	Does not bioaccumulate.
Diethylene Glycol 111-46-6		100	Leuciscus idus melanotus - 3 d - 0.05 mg/l

Page 7 of 9

SDS #63006400 Rev. January 7, 2016

12.4 Mobility in soil

Soil/water partition coefficient (Koc): Not available.

Mobility: Not available.

12.5 Results of PBT and vPvB assessment

PBT: Not available. vPvB: Not available.

12.6 Other adverse effects: No known significant effects or critical hazards. The ecological effects of this product have not been determined. The solvents in this product are not classified as toxic to aquatic organisms.

Section 13

DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal: Offer surplus and non-recyclable solutions to a licensed disposal company **Hazardous waste:** The classification of the product does not meet the criteria for a hazardous waste.

Contaminated Packaging

Methods of disposal: Dispose of as unused product. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions: Empty containers may contain product residue and may be dangerous.

RCRA 40 CFR 261 Classifications: As packaged and after use, it does not meet the criteria of a hazardous waste as defied under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, since it has neither the characteristics of Subpart C nor is listed in Subpart D.

Federal, State, and Local laws governing disposal of material can differ. Ensure proper disposal compliance with proper authorities before disposal.

Section 14

TRANSPORTATION INFORMATION

U.S. DOT Proper Shipping Name: Not regulated

DOT Hazard Class: None UN Number: None

IATA Proper Shipping Name: Not regulated

IATA Hazard Class: None UN Number: None

Section 15

REGULATORY INFORMATION

United States Federal Regulations:

MSDS complies with the OSHA Hazard Communication Rule, 29 CFR 1910.1200.

CERCLA/Superfund, 40 CFR 117, 302: None of the chemicals have a reportable quantity

Section 302 – Extremely hazardous substances (40 CFR 355): None of the chemicals are Section 302 hazards

Section 311/312 – Material Safety Data Sheet Requirements (40 CFR 370):

Hazard Categories: Immediate (acute) health, Delayed (chronic) health, Fire,

Section 313 - List of Toxic Chemicals (40CFC 372): This product contains 2-Butoxyethanol (CAS# 111-76-2) at a weight of 10 – 15% and Diethylene glycol butyl ether (CAS# 112-34-5) at a weight of 1 - 5% which are found on the 313 list of Toxic Chemicals.

Toxic Substance Control Act (TSCA): All substances are TSCA listed.

Resource Conservation and Recovery Act (RCRA 40 CFR 261) Subpart C & D: Refer to Section 13

SDS #63006400

Page 8 of 9

Rev. January 7, 2016

STATE REGULATIONS:

The following chemicals are specifically listed by individual state; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state

STATE CHEMICAL C.A.S. NUMBER WEIGHT % PA, NJ Diethylene glycol 111-46-6 1 - 5

California Proposition 65: This product does not contain chemicals which are known to the State of California to cause cancer, birth defects, or other reproductive harm.

INTERNATIONAL REGULATIONS: **Canada WHMIS:** This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR. All of the components of this product are listed on the Canadian Domestic substances List (DSL).

5.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization Substances of very high concern: None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable.

Sections 16

OTHER INFORMATION

NFPA Health: Can cause significant irritation

NFPA Fire: Will not burn NFPA Instability: Stable NFPA Reactivity: None



HMIS Health: Slight Hazard. Irritation or minor reversible injury possible. HMIS Flammability: Materials that must be preheated before ignition will occur.

Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

HMIS Reactivity: Minimal Hazard. Stable

HMIS Personal Protection: B. Safety glasses and protective gloves should be worn when handling this material.

LABEL INFORMATION: For Shipping Label information refer to section 14

- Keep out of the reach of children (S2)
- Caution: Contents under pressure

REVISION DATES, SECTIONS, REVISED BY:

27-Oct-08 Original release date, MKB

04-DEC-08 revision, mkb

14-Sept-09 EU format, new address, section 15, mkb 20-July-12 Updated flammability rating, section 2, mkb

11-Dec-14 Section 2, mkb

07-Jan-16 Updated GHS elements, mkb

ABBREVIATIONS USED IN THIS DOCUMENT:

NE – Not Established

NA – Not Applicable

NIF - No Information Found

F+ - Extremely Flammable

Xi - Irritant

Xn - Harmful

R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed

R22 - Harmful if swallowed

R36 - Irritating to eyes

R36/38 - Irritating to eyes and skin



Page 9 of 9

ABRIDGED LIST OF REFERENCES:

Code of Federal Regulations (CFR)
The Sigma-Aldrich Library of Regulatory and Safety Data
Chemical Guide and OSHA Hazardous Communication Standard
The Environmental Protection Agency (www.epa.gov)
American National Standards Institute

To the best of our knowledge, the information contained herein is accurate. However, neither ACL STATICIDE nor any of its subsidiaries assumes any liability **whatsoever for the accuracy or completeness of the information contained herein.** Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.