



## 8660 Staticide® Freeze Spray Anti-Stat

### *Safely Cools Static-Sensitive Components*


ACL's high-performance freeze spray quickly cools off printed circuit boards with pinpoint accuracy to help identify failed electrical components such as resistors, capacitors, and relays. Unique to this formula is an added anti-stat that prevents corrosion-causing frost. Static generation caused during the spray application is neutralized which prevents further damage to ESD-sensitive components.

Rapid cooling allows for high heat transfer between components making it ideal for identifying individual failed components, stress fractures, and cracks.

#### Directions:

First, power up the PCB. Spray product directly onto PCB with push nozzle for total board application. For isolating failures, use extension tube to systematically cool suspect components without freezing other areas of the board. When board begins to function, failed components have been identified. Use in conjunction with performance testing devices.

For industrial use only. Read SDS carefully prior to use.



*No corrosion-causing frost*

#### Ideal for the following applications:

- Rework and repair
- Electronics manufacturing and assembly
- PCB design

#### FEATURES:

- ❄️ Zero static generation
- ❄️ Non-flammable
- ❄️ Ultra pure; filtered to .020 microns
- ❄️ Fast-drying; non-residual
- ❄️ Non-corrosive; non-abrasive
- ❄️ Ozone-safe; no CFCs or HCFCs
- ❄️ Cools to -60°F/-51°C

Product# 8660

12 oz (340g) aerosol / 12 per case

